



HSM SP 4040 V

HSM SP 4040 V

- Combination device (FA 400.2 and KP 40V) especially compact and space-saving vertical design.
- Material intake via loading table and electric conveyor belt.
- Document shredder with keypad for continuous and reverse operation, as well as automatic reverse in the event of a paper jam.
- Shredding and pressing conducted simultaneously.
- Integrated, manual oiler for the cutting unit (particle cut version only).
- Press with modern control unit and removal trolley for box or waste bag (standard equipment: 5 boxes, 5 plastic bags, bag holder).
- Display to indicate “bale ready”.

Product type description	HSM SP 4040 V 5,8x50 3x400V	HSM SP 4040 V 5,8 3x400V
Order number	2514111124	2513111124
EAN Code	4026631028455	4026631028448
Cutting type	particle cut	strip cut
Security level	3	2
Cutting width	5.8 mm	5.8 mm
Particle length	50 mm	0 mm
Cutting capacity (70g/m ²)	120 sheet	130 sheet
Intake width	428 mm	428 mm
Cutting speed	220 mm/s	210 mm/s
eclass 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Working width	428 mm	428 mm
Order no. document shredder		1513644
Order no. baling press		6111164
Pressing power	44 kN	44 kN
Loading aperture width	510 mm	510 mm
Loading aperture height	320 mm	320 mm
Bale length	400,00 mm	400,00 mm
Bale width	600 mm	600 mm
Bale height	500 mm	500 mm
Power consumption of the motor	6200 W	6200 W
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Depth	2030 mm	2030 mm
Width	1090 mm	1090 mm
Height	1970 mm	1970 mm
Weight	737 kg	737 kg