



HSM V-Press 818

HSM V-Press 818

Thanks to its low transport height, the HSM V-Press 818 can be easily transported to wherever it needs to be used.

- Low installation height and surface
- High process reliability due to HSM TCS (TorsionControlSystem)
- Convenient membrane keypad with text display, which shows the current status of the machine
- Long service life due to low maintenance, reliable hydraulics and hard chromeplated piston rod

Product type description	V-Press 818 Plus	HSM V-Press 818 Eco
Order number	6150214	6150114
EAN Code	4026631034906	4026631035774
Pressing power	185 kN	185 kN
Specific pressing power	19.23 N/cm ²	19.23 N/cm ²
Press chamber depth	780 mm	780 mm
Loading height	871 mm	871 mm
Loading aperture width	1195 mm	1195 mm
Loading aperture height	530 mm	541 mm
Press chamber width	1200 mm	1200 mm
Bale length	1200,00 mm	1200,00 mm
Bale width	780 mm	780 mm
Bale height	700 mm	700 mm
Bale weight (max.)	200 kg	200 kg
Number of strappings	4	4
Strapping material	polyester tape	polyester tape
Cycle time in idle operation	35 s	35 s
Hourly bale output	2 - 5	2 - 5
Type of door	loading flap	double door
Door lock	handwheel	handwheel
Driving power	3 kW	3 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Depth	997 mm	997 mm
Width	1700 mm	1700 mm
Height	2370 mm	2370 mm
Weight	956 kg	994 kg
Order no. tape/wire	6212993010	6212993010