



HSM V-Press 860

HSM V-Press 860

With a pressing power of 532 kN and employing low-noise and energy-saving technology, the HSM V-Press 860 is the most economical and ecological solution for your waste disposal.

- Special retaining claws optimize the compression of the pressing material and reduce the number of loading actions
- Comfortable, easy-to-use membrane keypad with text display which show the current status of the machine

Product type description	HSM V-Press 860 eco	HSM V-Press 860 plus
Order number	6148134	6148234
EAN Code	4026631027601	4026631027724
Pressing power	532 kN	532 kN
Specific pressing power	56.83 N/cm ²	56.83 N/cm ²
Press chamber depth	780 mm	780 mm
Loading height	1100 mm	1100 mm
Loading aperture width	1195 mm	1195 mm
Loading aperture height	650 mm	650 mm
Press chamber width	1195 mm	1195 mm
Bale length	1200,00 mm	1200,00 mm
Bale width	780 mm	780 mm
Bale height	1200 mm	1200 mm
Bale weight (max.)	480 kg	480 kg
Number of strappings	4	4
Strapping material	wire	wire
Cycle time in idle operation	46 s	46 s
Hourly bale output	1 - 2	1 - 2
Type of door	double door	sliding door
Door lock	handwheel	handwheel
Driving power	7.5 kW	7.5 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Depth	1070 mm	1247 mm
Width	1797 mm	1797 mm
Height	2985 mm	2986 mm
Weight	1890 kg	2010 kg
Order no. tape/wire	6135993002	6135993002

HSM V-Press 860

Product type description	HSM V-Press 860 max
Order number	6148334
EAN Code	4026631027731
Pressing power	532 kN
Specific pressing power	56.83 N/cm ²
Press chamber depth	780 mm
Loading height	1100 mm
Loading aperture width	1195 mm
Loading aperture height	650 mm
Press chamber width	1195 mm
Bale length	1200,00 mm
Bale width	780 mm
Bale height	1200 mm
Bale weight (max.)	480 kg
Number of strappings	4
Strapping material	wire
Cycle time in idle operation	46 s
Hourly bale output	1 - 2
Type of door	sliding door
Door lock	hydraulic
Driving power	7.5 kW
Voltage	400 V
Frequency	50 Hz
Depth	1247 mm
Width	1797 mm
Height	2990 mm
Weight	2083 kg
Order no. tape/wire	6134993002