



HSM V-Press 860 S/P

HSM V-Press 860 S/P

The vertical baling press HSM V-Press 860 P is especially designed for the compression of opened or perforated PET/UBC bottles. The model HSM V-Press 860 S is the perfect machine for the volume reduction of stiff plastics (e.g. monitor and TV set housings) and expanding plastic film (other materials upon request).

- Double quantity of retaining claws optimize the compression of the pressing material and reduce the number of loading actions
- Reinforced press chamber and door lock
- Robust mechanical bale ejector belt or bale ejector chain
- Explosion protected model as per EX II G cb IIB T3 available on request (HSM V-Press 860 S)

Product type description	HSM V-Press 860 P	HSM V-Press 860 S
Order number	6148714	6148814
EAN Code	4026631027748	4026631027793
Pressing power	418 kN	418 kN
Specific pressing power	44.65 N/cm ²	44.65 N/cm ²
Press chamber depth	780 mm	780 mm
Loading height	1115 mm	1100 mm
Loading aperture width	1195 mm	1195 mm
Loading aperture height	650 mm	650 mm
Press chamber width	1195 mm	1195 mm
Bale length	1200,00 mm	1200,00 mm
Bale width	780 mm	780 mm
Bale height	1200 mm	1200 mm
Number of strappings	4	4
Strapping material	wire	wire
Cycle time in idle operation	46 s	46 s
Hourly bale output	1 - 2	1 - 2
Type of door	loading flap	double door
Door lock	hydraulic	hydraulic
Driving power	7.5 kW	7.5 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Depth	1273 mm	1076 mm
Width	1797 mm	1797 mm
Height	2985 mm	2985 mm
Weight	2282 kg	2284 kg
Order no. tape/wire	6135993002	6135993002