



HSM VK 2012

HSM VK 2012

- For industrial applications with medium material loads, e.g. processing industry, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput rate up to approx. 228 m³ / hour
- Low price solution for light goods up to approx. 40 kg/m³ bulk weight
- Particularly suitable for compressing lighter cardboard
- Large loading aperture suitable for bulky materials
- Suitable for continuous loading with conveyor belt, air feeding or similar
- Operating side can be selected
- Versatile use, also suitable for special materials (on request)
- Control of compression cycle via light barrier
- High compression and bale weights
- Integration

Product type description	HSM VK 2012	HSM VK 2012
Pressing power	240 kN	240 kN
Specific pressing power	42.9 N/cm ²	42.9 N/cm ²
Loading aperture width	620 mm	620 mm
Press chamber width	700 mm	700 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	700 mm	700 mm
Bale height	800 mm	800 mm
Bale weight (max.)	170 - 300 kg	170 - 300 kg
Number of strappings	4	4
Cycle time in idle operation	19.6 s	10.1 s
Driving power	9.2 kW	15 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	2350 mm	2350 mm
Height	2130 mm	2130 mm
Weight	4800 kg	4800 kg