



HSM VK 2306

HSM VK 2306

- For industrial applications with small to medium material loads, e.g. processing industry, PET bottles / UBC disposal, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput up to approx. 120 m³ / hour
- Similar to VK 12 series, with higher pressing power
- High bale density, higher bale weights
- Higher shearing forces
- Compresses paper, cardboard, foils and PET bottles / UBC
- Particularly suitable for PET / UBC compaction and for special applications
- Suitable for continuous loading
- Variety of uses
- Suitable for many different materials
- Operating side can be selected
- Control of compression cycle via light barrier
- Compact bale dimensions
- Low space requirement
- Approved system solution and technology

Product type description	HSM VK 2306	HSM VK 2306
Pressing power	240 kN	240 kN
Specific pressing power	68.6 N/cm ²	68.6 N/cm ²
Loading aperture width	620 mm	620 mm
Press chamber width	700 mm	700 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	700 mm	700 mm
Bale height	500 mm	500 mm
Bale weight (max.)	140 - 250 kg	140 - 250 kg
Number of strappings	3	3
Cycle time in idle operation	12.3 s	6.3 s
Driving power	9.2 kW	15 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	2600 mm	2600 mm
Height	2050 mm	2050 mm
Weight	7100 kg	7100 kg