



HSM VK 3008

HSM VK 3008

- For industrial applications with medium material loads, e.g. processing industry, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput rate up to approx. 244 m³ / hour
- Versatile solution for materials up to approx. 50 kg/m³ bulk weight
- Particularly suitable for compression of paper, cardboard and foils
- For fast cycle times, 800 mm loading aperture
- Suitable for continuous loading with conveyor belt, air feeding or similar
- Operating side can be selected
- Versatile use, also suitable for special materials (on request)
- Control of compression cycle via light barrier
- High compression and bale weights
- Integration

Product type description	HSM VK 3008	HSM VK 3008
Pressing power	310 kN	310 kN
Specific pressing power	55.4 N/cm ²	55.4 N/cm ²
Loading aperture width	620 mm	620 mm
Press chamber width	700 mm	700 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	700 mm	700 mm
Bale height	800 mm	800 mm
Bale weight (max.)	190 - 350 kg	190 - 350 kg
Number of strappings	4	4
Cycle time in idle operation	10.6 s	7.6 s
Driving power	15 kW	22 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	2350 mm	2350 mm
Height	2130 mm	2130 mm
Weight	5800 kg	5800 kg