



HSM VK 4208

HSM VK 4208

- For industrial applications with medium material loads, e.g. processing industry, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput rate up to approx. 247 m³ / hour
- Versatile solution for materials up to approx. 60 kg /m³ bulk weight
- Suitable for compressing paper, cardboard, shredded material and foils
- For fast cycle times
- Suitable for continuous loading with conveyor belt, air feeding or similar
- Operating side can be selected
- Versatile use, also suitable for special materials (on request)
- Control of compression cycle via light barrier
- High compression and bale weights
- Integration

Product type description	HSM VK 4208 (22kW)	HSM VK 4208 (30kW)
Pressing power	420 kN	420 kN
Specific pressing power	75 N/cm ²	75 N/cm ²
Loading aperture width	620 mm	620 mm
Press chamber width	700 mm	700 mm
Bale length	600 - 1203 mm	600 - 1205 mm
Bale width	700 mm	700 mm
Bale height	800 mm	800 mm
Bale weight (max.)	220 - 420 kg	220 - 420 kg
Number of strappings	4	4
Cycle time in idle operation	9.6 s	7.6 s
Driving power	22 kW	30 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	2350 mm	2350 mm
Height	2130 mm	2130 mm
Weight	5800 kg	5800 kg