



HSM VK 4812

HSM VK 4812

- For industrial applications with medium material loads, e.g. processing industry, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput up to approx. 301 m³ / hour
- For materials up to approx. 60 kg/ m³ bulk weight
- With large loading aperture and higher pressing power
- Large bales and higher bale weights
- Suitable for continuous loading with conveyor belt, air feeding or similar
- Operating side can be selected
- Versatile use, also suitable for special materials (on request)
- Control of compression cycle via light barrier
- High compression and bale weights
- Integration

Product type description	HSM VK 4812	HSM VK 4812
Pressing power	480 kN	480 kN
Specific pressing power	58.2 N/cm ²	58.2 N/cm ²
Loading aperture width	1020 mm	1020 mm
Press chamber width	1100 mm	1100 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	1100 mm	1100 mm
Bale height	750 mm	750 mm
Bale weight (max.)	300 - 550 kg	300 - 550 kg
Number of strappings	4	4
Cycle time in idle operation	21.2 s	16.5 s
Driving power	15 kW	22 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	3750 mm	3750 mm
Height	2400 mm	2400 mm
Weight	10000 kg	10000 kg