



HSM VK 6015

HSM VK 6015

- For industrial applications with special requirements, e.g. processing industry, disposal companies, PET bottles / UBC disposal, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput up to approx. 326 m³ / hour
- Very high specific pressure - for high compaction
- High shearing force
- Versatile system also for materials with bulk weights higher 60 kg / m³
- Particularly suitable for compression of paper, cardboard, foils, production remains, e.g. trimmings from a variety of materials
- For continuous loading
- 4-fold strapping for optimised bale result
- Optimised bale dimensions and bale weights for efficient truck loading
- Large loading apertures, quick mode of operation
- Control of compression cycle via light barriers
- High compression and bale weights
- Approved system solution and technology

Product type description	HSM VK 6015	HSM VK 6015
Pressing power	580 kN	580 kN
Specific pressing power	111.9 N/cm ²	111.9 N/cm ²
Loading aperture width	640 mm	640 mm
Press chamber width	720 mm	720 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	720 mm	720 mm
Bale height	720 mm	720 mm
Bale weight (max.)	250 - 450 kg	250 - 450 kg
Number of strappings	4	4
Cycle time in idle operation	17.5 s	12 s
Driving power	30 kW	45 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	3230 mm	3230 mm
Height	2870 mm	2870 mm
Weight	14500 kg	14500 kg

HSM VK 6015

Product type description	HSM VK 6015
Pressing power	580 kN
Specific pressing power	111.9 N/cm ²
Loading aperture width	640 mm
Press chamber width	720 mm
Bale length	600 - 1200 mm
Bale width	720 mm
Bale height	720 mm
Bale weight (max.)	250 - 450 kg
Number of strappings	4
Cycle time in idle operation	9.4 s
Driving power	55 kW
Voltage	400 V
Frequency	50 Hz
Width	3230 mm
Height	2870 mm
Weight	14500 kg