



HSM VK 7215

HSM VK 7215

- For professional disposal or larger industrial applications - with high throughput rates, e.g. processing industry, disposal companies, PET bottles / UBC disposal, department stores, document shredding facilities, printing and paper industry
- Suitable for applications with a throughput rate up to approx. 505 m³ / hour
- Versatile system also for materials with bulk weights higher 60 kg / m³
- For professional disposal management o larger industrial applications
- High throughput capacity
- For cardboard, paper, foils, DSD goods, PET bottles / UBC (and much more on request)
- For continuous loading
- 1500 mm loading aperture
- 5-fold strapping for optimised bale result
- Optimised bale dimensions and bale weights for efficient truck loading
- Large loading aperture, quick mode of operation
- Control of compression cycle via light barriers
- High compression and bale weights
- Approved system solution and technology
- Available as an option with frequency-regulated drive – saves 40% of the energy used by standard drives

Product type description	HSM VK 7215	HSM VK 7215
Pressing power	720 kN	720 kN
Specific pressing power	87.3 N/cm ²	87.3 N/cm ²
Loading aperture width	990 mm	990 mm
Press chamber width	1100 mm	1100 mm
Bale length	600 - 1200 mm	600 - 1200 mm
Bale width	1100 mm	1100 mm
Bale height	750 mm	750 mm
Number of strappings	5	5
Cycle time in idle operation	12.9 s	9.3 s
Driving power	55 kW	75 kW
Voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Width	3970 mm	3970 mm
Height	3000 mm	3000 mm
Weight	23500 kg	23500 kg

HSM VK 7215

Product type description	HSM VK 7215
Pressing power	720 kN
Specific pressing power	87.3 N/cm ²
Loading aperture width	990 mm
Press chamber width	1100 mm
Bale length	600 - 1200 mm
Bale width	1100 mm
Bale height	750 mm
Number of strappings	5
Cycle time in idle operation	8.8 s
Driving power	90 kW
Voltage	400 V
Frequency	50 Hz
Width	3970 mm
Height	3000 mm
Weight	23500 kg