



HSM SECURIO P44

HSM SECURIO P44

Mobile, highest performance model for open-plan offices. Multi-function operating button, reversing button and integrated button lock. Auto-reverse in the event of a paper jam. Folding safety element with contact protection and integrated service flap. Automatic oiler for cutting unit (particle cut version only). Separate CD cutting unit (security level 3) and metal detection, depending on security level. Economic energy management (EMCS). Integrated PAPERcontrol function prevents paper jams. Filling level display through inspection window. Large collection volume. With removable, reusable waste bag. Special CD waste container for correctly sorted separation of the shredded material (optional). Made in Germany.

Product type description	SECURIO P44 3,9 mm	SECURIO P44 5,8 mm
Order number	1870111	1871111
EAN Code	4026631032032	4026631032025
Shredder material		
Cutting type	strip cut	strip cut
Security level	2	2
Cutting width	3.9 mm	5.8 mm
Particle length		
Cutting capacity (70g/m ²)	61-63 sheet	76-78 sheet
Cutting capacity (80g/m ²)	56-58 sheet	70-72 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	66 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	105 kg

HSM SECURIO P44

Product type description	SECURIO P44 3,9x40 mm	SECURIO P44 1,9x15 mm
Order number	1873111	1872111
EAN Code	4026631032049	4026631032056
Shredder material		
Cutting type	particle cut	particle cut
Security level	3	4
Cutting width	3.9 mm	1.9 mm
Particle length	40,00 mm	15,00 mm
Cutting capacity (70g/m²)	43-46 sheet	28-30 sheet
Cutting capacity (80g/m²)	39-41 sheet	23-25 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	66 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	105 kg

HSM SECURIO P44

Product type description	SECURIO P44 3,9x40mm CD	SECURIO P44 3,9x50 mm OMDD
Order number	1873111C	1873111M
EAN Code	4026631032070	4026631032100
Shredder material		
Cutting type	particle cut	particle cut
Security level	3	3
Cutting width	3.9 mm	3.9 mm
Particle length	40,00 mm	40,00 mm
Cutting capacity (70g/m²)	43-46 sheet	43-46 sheet
Cutting capacity (80g/m²)	39-41 sheet	39-41 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	111 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 1,9x15 mm CD	SECURIO P44 1,9x15 mm OMDD
Order number	1872111C	1872111M
EAN Code	4026631032087	4026631032117
Shredder material		
Cutting type	particle cut	particle cut
Security level	4	4
Cutting width	1.9 mm	1.9 mm
Particle length	15,00 mm	15,00 mm
Cutting capacity (70g/m²)	28-30 sheet	28-30 sheet
Cutting capacity (80g/m²)	23-25 sheet	23-25 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	66 dB	66 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	111 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 0,78x11 mm	SECURIO P44 0,78x11mm CD
Order number	1875111	1875111C
EAN Code	4026631036658	4026631036665
Shredder material		
Cutting type	particle cut	particle cut
Security level	5	5
Cutting width	0.78 mm	0.78 mm
Particle length	11,00 mm	11,00 mm
Cutting capacity (70g/m²)	18-19 sheet	18-19 sheet
Cutting capacity (80g/m²)	15-16 sheet	15-16 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
eclass 5.1		24320704
UN/SPSC		
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 0,78x11 mm metal detection	SECURIO P44 0,78x11 mm CD + metal detection
Order number	1875111D	1875111E
EAN Code	4026631036788	4026631036795
Shredder material		
Cutting type	particle cut	particle cut
Security level	5	5
Cutting width	0.78 mm	0.78 mm
Particle length	11,00 mm	11,00 mm
Cutting capacity (70g/m²)	18-19 sheet	18-19 sheet
Cutting capacity (80g/m²)	15-16 sheet	15-16 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
eclass 5.1		
UN/SPSC		
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 0,78x11 mm OMDD	SECURIO P44 0,78x11 mm OMDD + metal detection
Order number	1875111M	1875111N
EAN Code	4026631036771	4026631036801
Shredder material		
Cutting type	particle cut	particle cut
Security level	5	5
Cutting width	0.78 mm	0.78 mm
Particle length	11,00 mm	11,00 mm
Cutting capacity (70g/m ²)	18-19 sheet	18-19 sheet
Cutting capacity (80g/m ²)	15-16 sheet	15-16 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
eclass 5.1		
UN/SPSC		
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	111 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 1x5 mm	SECURIO P44 1x5 mm CD
Order number	1874111	1874111C
EAN Code	4026631032063	4026631032094
Shredder material		
Cutting type	particle cut	particle cut
Security level	HS Level 6	HS Level 6
Cutting width	1 mm	1 mm
Particle length	5,00 mm	5,00 mm
Cutting capacity (70g/m ²)	12 sheet	12 sheet
Cutting capacity (80g/m ²)	10 sheet	10 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 1x5 mm metal detection	SECURIO P44 1x5 mm CD + metal detection
Order number	1874111D	1874111E
EAN Code	4026631032131	4026631032148
Shredder material		
Cutting type	particle cut	particle cut
Security level	HS Level 6	HS Level 6
Cutting width	1 mm	1 mm
Particle length	5,00 mm	5,00 mm
Cutting capacity (70g/m ²)	12 sheet	12 sheet
Cutting capacity (80g/m ²)	10 sheet	10 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	111 kg

HSM SECURIO P44

Product type description	SECURIO P44 1x5 mm OMDD	SECURIO P44 1x5 mm OMDD + metal detection
Order number	1874111M	1874111N
EAN Code	4026631032124	4026631032155
Shredder material		
Cutting type	particle cut	particle cut
Security level	HS Level 6	HS Level 6
Cutting width	1 mm	1 mm
Particle length	5,00 mm	5,00 mm
Cutting capacity (70g/m ²)	12 sheet	12 sheet
Cutting capacity (80g/m ²)	10 sheet	10 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	67 dB	67 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	111 kg	111 kg